



Presenting A Multipurpose Bonding Agent To Revolutionize
The Building And Tiling Industry.



FIRMA AGENT

298 | MULTI-PURPOSE BONDING AGENT

FIRMA AGENT is designed as a Multi - Purpose Bonding Agent most suitable for modifying Ordinary Portland Cement compositions.

FIRMA AGENT a bluish water - based emulsion admixture has an exceptionally high bonding strength when combined with Ordinary Portland Cement Plaster.



19 Litres
(5 US Gallon)

4 Litres
(1 US Gallon)

*Every Smooth Surface
(SHEAR WALL, GLASS, PLYWOOD)
Prior to wall plastering and tiling work require a coating of
FIRMA AGENT 298*

ADVANTAGES

Eliminates the application of 'Spatter Dash' or commonly call as pre-grout / stamping / chopping for shear wall plastering

High bonding performance even laying tiles on plywood, glass or other unconventional surfaces

Enormous time saving, cost saving over conventional resurface work system

SIMPLICITY -
Add only OPC & WFS for installing Porcelain Tiles



FIRMA AGENT

298 | MULTI-PURPOSE BONDING AGENT



APPLICATIONS

FIRMA AGENT high bonding strength is most suitable for the following applications;


A. TILING WORK

- i) Lay all types of tiles, marble and stone on floor and wall
- ii) Renovation work lay tiles on tiles
- iii) Lay tiles on wooden surfaces (plywood, cement board)
- iv) Unconventional surfaces : Lay tiles on glasses


B. OTHER APPLICATION

- i) To bond old and new concrete together (eg: defects work)

A. CASTING VERTICAL CONCRETE



B. CASTING FLOOR WITH 1/2" to 2+" CONCRETE TOPPING



PROCEDURES

- Identify one layer or two layer of FIRMA AGENT 298 for application
- Clean working surface from excessive dust
- Apply FIRMA AGENT 298 on the working surface using a brush / roller on its designated area
- Allow at least 20 minutes of drying time before proceed working on the surface coated with FIRMA AGENT 298
- Effective Time - The surface area coated with FIRMA AGENT 298 may be left for up to seven (7) days before the actual laying of tiles or other applications

(It is necessary to apply a new coat of FIRMA AGENT 298 over the previous coating if passed the 7 Days Effective Time)

Remark:

FIRMA AGENT 298 may be used with admixture of OPC only AND / OR, optionally added Washed Fine Sand and MH PRO 299 Cement Enhancer into the admixture of OPC & water to produce added - strength's mortar when required for certain applications.

